

TNC F/F Coaxial RF Surge Protector, DC - 50MHz, 1W, IP67, 15 V Max., 1mJ, 20kA, Hybrid, Bracket Down, Hole Mount



AGX+15TFTF-A

Features

- Surge current of 20kA
- Max Power 1W
- Frequency range from 0 to 50 MHz
- TNC-type Female connectors
- Waterproof IP67 rated
- DC Pass
- VSWR <1.2:1
- CE & RoHS compliant
- Directional

Applications

- WiFi
- GPS
- Land mobile radio

Description

RF surge protector (also known as lightning arrester or surge arrester) AGX+15TFTF-A from PolyPhaser, utilizes a patented hybrid protection technology integrating a silicon avalanche suppression diode (SASD), a Metal Oxide Varistor (MOV) and a gas tube (GT or GDT). This RF surge protector component is manufactured in a coaxial in-line design with wide operating frequency range. All PolyPhaser RF surge protector products are available in stock with same day shipping.

Electrical Specifications

Surge Protector Type
DC Handling

Hybrid
DC Pass

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		50	MHz
Impedance		50		Ohms
VSWR			1.1:1	
Insertion Loss			0.3	dB
Operating Voltage (DC)			15	Volts
Input Power, CW			1	Watt
Surge Current IEC 61000-4-5 8/20µs waveform multiple			20	kA
Turn On Voltage		19		Volts
Throughput Energy for 3kA @ 8/20µs waveform			1	mJ

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[TNC F/F Coaxial RF Surge Protector, DC - 50MHz, 1W, IP67, 15 V Max., 1mJ, 20kA, Hybrid, Bracket Down, Hole Mount AGX+15TFTF-A](#)

TNC F/F Coaxial RF Surge Protector, DC - 50MHz, 1W, IP67,
15 V Max., 1mJ, 20kA, Hybrid, Bracket Down, Hole Mount



AGX+15TFTF-A

Mechanical Specifications

Size

Length	2.72 in [69.09 mm]
Width/Diameter	2.83 in [71.88 mm]
Height	1.44 in [36.58 mm]

Configuration

Input Connector	TNC Female
Output Connector	TNC Female

Environmental Specifications

Temperature

Operating Range	-50 to 50 deg C
Storage Range	-50 to +85 deg C

Ingress Protection (IP) Rating	IP67
Humidity	95%

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[TNC F/F Coaxial RF Surge Protector, DC - 50MHz, 1W, IP67, 15 V Max., 1mJ, 20kA, Hybrid, Bracket Down, Hole Mount AGX+15TFTF-A](#)

TNC F/F Coaxial RF Surge Protector, DC - 50MHz, 1W, IP67, 15 V Max., 1mJ, 20kA, Hybrid, Bracket Down, Hole Mount



AGXZ+15TFTF-A

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[TNC F/F Coaxial RF Surge Protector, DC - 50MHz, 1W, IP67, 15 V Max., 1mJ, 20kA, Hybrid, Bracket Down, Hole Mount AGXZ+15TFTF-A](#)



TNC F/F Coaxial RF Surge Protector, DC - 50MHz, 1W, IP67, 15 V Max., 1mJ, 20kA, Hybrid, Bracket Down, Hole Mount



AGX+15TFTF-A



PolyPhaser protects and increases the reliability of global RF communications networks, including transportation, telecommunications, defense, security and industrial applications, with superior RF surge protection technologies including DC Block, DC Pass and Ultra Low PIM. Backed by responsive service and expert technical support PolyPhaser continually expands its product offering and services to serve engineers' urgent needs for RF components in mission critical communication networks.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC F/F Coaxial RF Surge Protector, DC - 50MHz, 1W, IP67, 15 V Max., 1mJ, 20kA, Hybrid, Bracket Down, Hole Mount AGX+15TFTF-A](https://www.polyphaser.com/tnc-surge-protector-50mhz-hybrid-agxz-15tftf-a)

URL: <https://www.polyphaser.com/tnc-surge-protector-50mhz-hybrid-agxz-15tftf-a>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. PolyPhaser reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. PolyPhaser does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and PolyPhaser does not assume any liability arising out of the use of any part or documentation.

TNC F/F Coaxial RF Surge Protector, DC - 50MHz, 1W, IP67, 15 V Max., 1mJ, 20kA, Hybrid, Bracket Down, Hole Mount

AGXZ+15TFTF-A CAD Drawing

